

# Product Summary

## NOM-Certified Products

→ © 2007 Publication of The Bodine Company Inc.

03/27/07 • L0000300

Model Number	Lumen Output	Lamps Operated	Wattage Range	Types of Lamps Operated	Ballast Dimensions (L x W x H)	Mounting Center
B50	1100-1400	1 2	17 - 215 W 17 - 40 W	(2'-8') T8s, T9s, T10s or T12s; (4-pin) long compacts	13.3" X 2.4" X 1.5" (339 mm X 60 mm X 38 mm)	12. 8" ( 325 mm)
B60	600-700	1 2	17 - 215 W 17 - 40 W	(2'-8') T8s, T9s, T10s or T12s; (4-pin) long compacts	9.4" X 2.4" X 1.5" (238 mm X 60 mm X 38 mm)	8.9" (226 mm)
B100	350-450	1	17 - 40 W	(2'-4') T8, T9, T10 or T12; (4-pin) long compact	9.4" X 2.4" X 1.5" (238 mm X 60 mm X 38 mm)	8.9" (226 mm)
BDL94C <sup>12</sup>	300-750	1 2	13 - 42 W 13 - 38 W	(4-pin) twins, quads or triple twin-tubes	9.4" X 2.4" X 1.5" (238 mm X 60 mm X 38 mm)	8.9" (226 mm)
B413 <sup>1</sup>	200-625	1	5 - 13 W	(2-pin) twin or quad	9.4" X 2.4" X 1.5" (238 mm X 60 mm X 38 mm)	8.9" (226 mm)
LP550 <sup>1</sup>	390-700	1	14 - 55 W	Standard or HO T5 or T8	18.5" X 1.18" X 1.18" (470 mm X 30 mm X 30 mm)	18.1" (460 mm)

Linear

Compact

Low Profile

<sup>1</sup>Specification sheets and installation instructions for these NOM-Certified products are not yet available. Please see the specification sheets and installation instructions for their non-NOM-Certified counterparts.

<sup>2</sup>The BDL94C may not properly operate low mercury compact lamps.



Sales 800.223.5728



Fax 901.853.5009



www.bodine.com

**bodine**®